



EMULSION SPRAYER



acmar
On the road with you

The mini sprayer on skid or on trailer

Spraying

- ▶ Spraying by air pressure.
- ▶ Equipment in accordance with the EU Pressure Equipment directive PED 97/23 and is not subject to regular control.
- ▶ Diesel motor-compressor unit
- ▶ Hand lance with conical jet, swivel union between lance and hose.
- ▶ 10 m hose fitted on automatic winch
- ▶ Extremely easy to use.
- ▶ **Optional** : Spray bar

Storage / Heating

- ▶ Insulated cylindrical tank, capacity of 500, 1 000, 1 500 or 2 000 L.
- ▶ Direct heating with manual fuel burner.
- ▶ Equipment under 3,5T, mounted on self-braking chassis.
- ▶ **Optional** : automatic starter and regulation burner ; overnight heating with electric rods on 220 or 380 V



Type	Capacity (L)	Measures (mm)**	Unload weight (kgs)	G.V.W. (kgs)
Towed	500	3850 x 1490 x 1600	750*	1300
Removable	500	2310 x 1210 x 1250	490*	990
Towed	1000	4850 x 1580 x 1900	1000*	2500
Removable	1000	3050 x 1580 x 1400	610*	1610
Towed	1500	4850 x 1580 x 1900	1000*	2500
Removable	1500	3050 x 1580 x 1500	670*	2170
Towed	2000	5700 x 1580 x 1950	1500*	3500
Removable	2000	3650 x 1580 x 1500	765*	2765

* depending of options

** If possible, we can adapt our equipment to the dimensions of your hopper or your flat chassis.

Optional

- ▶ Heat lagging protection coat in stainless steel instead of aluminium
- ▶ Motor-compressor unit electric starter.
- ▶ Binder pump spraying mode (not compatible with spray bar)
- ▶ Lights dual voltage 12/24V device
- ▶ Extinguisher
- ▶ Hand lance jet cone