









A spraying of quality for your surface dressing and patching

- Isolated tank of up to 5 000 liters
- Direct heater with automatic burner
- ▶ 35m³/h heated binder pump
- 3 m spray bar with hydraulic opening (two extensions)
- Stainless steel pneumatic jets, removable, with indexed nozzles, 125 mm centerline (triple overlap)
- Dosage from 0,2 up to 2 l/m²
- ▶ Hand lance

High quality chippings spreading

- ▶ 6,5 m³ hopper
- ▶ 80% of the job done with hopper in down position
- 3 m automatic chippings spreader (two extensions)
- Chippings from 2 to 15 mm
- Dosage from 2,5 to 12 l/m²
- ▶ Chippings boxes for shovel jobs
- Optionnal :

• 3,5 tons or heavy duty hook



Security / Maintenance

- Filling dome acces with safety platform
- Services and maintenance thought from the conception of the machine
- All elements accessible from the ground
- Automated cleaning device without any binder rejection to the ground





Computer: SMART16



- ▶ Tropicalized computer SMART16 in cab with controls on ergonomic arm
- ▶ Programming of binder dosage
- ▶ Binder pump speed regulation
- Individual jets and gates On/Off through switches box
- Archiving and monitoring of jobs data (surface, dosage, job name ...)
- Optional :
 - Sighting device for patching
 - Printer



