



ACMAR



COMBINED SPRAYER

EXPORT - RGM3

Tél. +33 (0)2 43 06 14 28
info@acmar.fr

acmar.fr



EXPERIENCE AND HIGH TECHNOLOGY FOR YOUR SURFACE DRESSINGS

Mounted on 6 wheeler truck



A SPRAYING OF QUALITY FOR YOUR SURFACE DRESSING

- Insulated emulsion tank up to 5 000 L
- Direct heating with automatic fuel burner
- 50 m³/h heated binder pump
- 3m spray bar with hydraulic opening (2 extensions)
- Stainless steel pneumatic jets, removable, 125 mm centerline for a triple overlap on the ground
- Dosage from 0.2 to 2.5 L/m²
- Hand lance



SECURITY / MAINTENANCE / RESPECT OF THE ENVIRONMENT

- Filling dome access with safe platform
- Care and maintenance designed from the conception of the machine
- Elements positioned consistently and all accessible from the ground
- Automatic cleaning device without any binder rejection on the ground
- Optional: rearview camera



HIGH QUALITY CHIPPINGS SPREADING

- 6,5 m³ tipper hopper
- 80% of the job done with hopper in down position
- 3 m automatic chippings spreader (2 extensions) télescopiques
- Chippings from 2 to 15 mm
- Dosage from 2,5 L/m² to 16 L/m²
- Chippings boxes for shovel jobs
- Optional: 3,5T and/or heavy duty hook



SMART₁₆ COMPUTER

- SMART₁₆ computer in the cab with controls on ergonomic arm
- Programming of binder dosages
- Binder pump speed
- Individual jet and date On/Off through switches box
- Archiving and monitoring of jobs data (surface, dosage, job name...)
- Optional : printer ; sighting device for patching